



IN-CEILING/ eIC Series

In-Ceiling/In-Wall Loudspeakers

APPLICATIONS

- Corporate and residential buildings
- Commercial premises
- Leisure centres
- Health and sports centres
- Meeting and conference rooms
- Auditoriums, museums

eIC52MS:

- Saunas, spas, ships, harbors, etc

eIC51-F/eIC51/eIC52/eIC5154/eIC52MS is a cost-effective in-ceiling installation loudspeaker with a great sound performance.



eIC51-F



eIC51-F Fast mount system



eIC51



eIC52



eIC52MS



eIC5154



KEY FEATURES

- Built-in audio transformer for 70/100 V use
- EN54-24 Certified (eIC5154)
- Suitable for installations exposed to extreme humidity and/or temperature (eIC52MS)
- EASE Win file available

	eIC51-F	eIC51	eIC52	eIC5154	eIC52MS
RMS power / Program power (8Ω)	-	10W / 20W	20W / 40W	-	20 / 35W
Woofers / tweeter	5" / -	5,25" / -	5,25" / 0,75"	5" / -	5" / 1"
Power selector @ 100V	3/6 W	3/6 W	3/6 W	0,38/0,75/1,5/3/6 W	-
SPL 1W/1m	TBC	88 dB	86 dB	92 dB	89 dB
Dimensions / Weight	∅ (internal)x ∅ (external) xD: 155x175x50 / 400 g.	∅ (internal)x ∅ (external) xD: 164x202x60mm / 0,9 kg.	∅ (internal)x ∅ (external) xD: 164x202x65mm / 1,0 kg.	∅ (internal)x ∅ (external) xD: 158x180x147mm / 1,2 kg.	∅ (internal)x ∅ (external) xD: 120x165x60mm / 0,6 kg.