



APPLICATIONS

eMOTUS5P / eMOTUS5PB:

- Education Classrooms
- Commercial premises
- Leisure centres
- Sound reinforcement in clubs, bars, etc.
- Health and sports centres
- Meeting and conference rooms
- Auditoriums, museums

eMOTUS50D:

- Theme parks
- Gardens, nature parks and urban spaces
- Leisure centers
- Health and sport centers
- Museums
- Residential buildings, outdoor areas

The eMOTUS5P/eMOTUS5PB is a kit of loudspeakers including an active and a passive acoustic box. The eMOTUS5PB includes a wireless BT receiver, remote control and remote control volume port (0-10 VDC). A compact, professional stereo kit, easy to handle and at a very attractive price. Its fantastic performance and unique design ensure that it can easily be integrated into a wide range of multimedia applications: lecture halls, meeting rooms, outlets, etc. Available in black and white.

eMOTUS50D is a 5" loudspeaker designed for installing outdoor. A compact, professional loudspeaker with great performance at a highly attractive price. Its fantastic performance and unique design mean that it can easily be integrated into a wide range of applications: theme parks, urban spaces, gardens, etc. Available in black and white.

ACCESSORIES



- WPa series (eMOTUS5PB)



eMOTUS5PB
Slave unit

eMOTUS5PB
Remote controller



eMOTUS5PB
Master unit



KEY FEATURES

eMOTUS5P / eMOTUS5PB:

- Stereo 2-way loudspeaker stereo kit – powered loudspeaker + passive loudspeaker
- Full range: 5" woofer and 1" tweeter
- Integrated amplifier 2 x 25 WRMS (MASTER unit)
- Volume control and tone control (bass & treble) in the MASTER unit
- Euroblock balance stereo input on the MASTER UNIT
- Non-balanced RCA input on the MASTER UNIT
- Wireless BT stereo input (only on the eMOTUS5PB)
- Mono/Stereo switch
- Link between the MASTER and the SLAVE unit via Euroblock connectors.
- Integrated power supply source (MASTER unit)
- Selectable power voltage 115 V/230 V (MASTER unit)
- Auto standby function (automatic standby mode / energy saving without the need to turn the system on or off each day)
- Integrated Anti-Clip System
- LED activity display
- Reinforced ABS construction
- BT wireless connection, remote control port (0-10 VDC – RJ45 connector) and remote control (eMOTUS5PB)
- Available in black and white

eMOTUS50D:

- 2-way cabinet, 5" woofer and 1" tweeter
- 40WRMS @ 8Ω
- Power selector: 3,75 / 7,5/ 15 / 30W @ 100V & 8Ω position
- Outdoor design
- IP65 rated
- Back rubber cover for connections
- Available in black and white colour



eMOTUS5P Front



eMOTUS5P Slave unit rear



eMOTUS5P Master unit rear



eMOTUS0D Front



eMOTUS0D Rear with rubber cover for connections

	eMOTUS5P	eMOTUS5PB	eMOTUS50D
RMS power / Program power	2 x 25W / 2 x 50W	2 x 25W / 2 x 50W	40W / 80W (8Ω)
Power selector @ 100V	-	-	7,5/15/30 W
Audio inputs	2 ST LINE (bal. & unbal.)	2 ST LINE (bal. & unbal.) + BT	-
Others	Bass & treble EQ + ST/MONO switch	IR + Remote port + Bass & treble EQ + ST/MONO switch	IP65 + paintable
Dimensions / Weight	HxWxD: 180x173x185mm / 4,2 kg.	HxWxD: 180x173x185mm / 4,8 kg.	HxWxD: 180x173x181mm / 4,8 kg.