



APPLICATIONS

- Gyms
- Restaurants
- Retail shops
- Boardrooms and conference centres
- Education centres

ACCESSORIES



■ MPAGE1r



■ WPaMIX-T

They include a 3 band tone control section, Talkover (priority) function assignable to each MIC/LINE input over the mix bus, ST/MONO mix switch and MUTE port for external dry contact triggering.

eSAM402 is an installation audio mixer in standard rack format, featuring 3 MIC/LINE ST inputs, 1 LINE ST input, 1 main mix output and one AUX/REC additional output.

eSAM702 is an installation audio mixer in standard rack format, featuring 6 MIC/LINE ST inputs, 1 LINE ST input, 1 main mix output and one AUX/REC additional output.

eSAM603 is an installation audio mixer in standard rack format, featuring 1 MIC input, 4 MIC/LINE ST inputs, 1 LINE ST input, 1 ST output (A/B) and 1 MONO output (C). A/B output can operate in ST/MONO mode. Each input can be routed to output A, B and/or C.



eSAM402



eSAM702



eSAM702



eSAM603



eSAM603



KEY FEATURES

eSAM series:

- 19" installation mixer
- MIC/LINE ST inputs & LINE ST inputs (eSAM603: additional MIC input)
- eSAM402 & eSAM702: 1 main mix output and one AUX/REC additional output.
- eSAM603: 1 ST/2 MONO main mix output and one MONO output. One AUX/REC additional output
- eSAM402 & eSAM702: 3 band tone control section.
- eSAM603: 2 x 3-band tone control section (A/B and C)
- Talkover (priority) function assignable from each MIC/LINE input over the mix
- Micro sensitivity level can be adjusted on the back panel
- +18V Phantom Power available for all MIC inputs

	eSAM402	eSAM702	eSAM603
Inputs	3 MIC/ST LINE + 1 ST LINE	6 MIC/ST LINE + 1 ST LINE	4 MIC/ST LINE + 1 MIC + 1 ST LINE
Outputs	1 MAIN ST + 1 AUX/REC	1 MAIN ST + 1 AUX/REC	1 MAIN ST / 2 MONO (selectable) + 1 MONO + AUX/REC
Tone control	Bass, mid & treble (mix)	Bass, mid & treble (mix)	Bass, mid & treble (per mix)
Remote control	MUTE contact	MUTE contact	MUTE contact
Dimensions / Weight	HxWxD: 44 (1RU)x482,6x120mm / 1,7 kg.	HxWxD: 44 (1RU)x482,6x120mm / 1,8 kg.	HxWxD: 44 (1RU)x482,6x195mm / 2,1 kg.