

HSA300

HIGH IMPEDANCE

High Impedance Mono Amplifier



PRODUCT OVERVIEW

The HSA300 is a single channel amplifier with direct 100 V line (high impedance) output. It's equipped with Ecler's proprietary SPM 100 Technology - Channel N, which allows for 100 V speaker lines connection without using 100 V line transformers, as this kind of amplifiers usually do. This fact has many advantages, being the main one the excellent audio quality, specially improved in the low-end frequencies when compared to classical 100V line amplifiers.


KEY FEATURES

- 1 mono balanced input
- 1 x 300 WRMS output (100V line level)
- Euroblock connectors
- SPM 100 amplification Technology - Channel N (no 100V output transformers used):
 - Improved frequency response (specially at the low-end)
 - Great efficiency
 - Low weight
- Butterworth, 3rd order high pass filter @ 70Hz
- Thermal protection
- Overload protection
- Anti-clip system
- Volume control knobs on front panel with protection cap, against undesired manipulation

APPLICATIONS

- Single or multi-zone BGM and paging systems with 100V line speakers, combined with the DAM, MIMO and SAM / eSAM series preamplifiers / processors

MECHANICAL DIAGRAMS



TECHNICAL DATA

Power Output		
RMS Power @ 10% THD	302 WRMS @ 100V line	
RMS Power @ 1% THD:	254 WRMS @ 100V line	
Frequency response (-1dB, -3dB)	30Hz - 35kHz	
Filter (High-Pass) 3rd order Butterworth	70Hz	
THD+Noise @ 1kHz Full Power	<0.07%	
SNR	>85dB	
Damping factor 1kHz @ 8Ω	N/A	
Input sensitivity / Impedance	0dBV/>20k	
Anticlip @ 2ddBV input	N/A	
Mains voltage	115V/230V. Voltage changed internally (NOT BY SWITCH)	
Power consumption		
pink noise, 1/8 power	218VA @ 32Ω	
pink noise, 1/3 power	319VA @ 32Ω	
Dimensions	482.6x88x285mm / 3,46 x 19 x 11,22 in	
Weight	8,4 kg / 18.51 lb	