

IC6

CEILING LOUDSPEAKERS

In-ceiling / In-wall Loudspeaker




PRODUCT OVERVIEW

With its discreet design, the IC6 2-way loudspeaker is the perfect option for 70/100 V and low impedance sound solutions. It mounts a 6.5" woofer and a 1" tweeter.

IC series provide excellent sound quality thanks to their infinite baffle philosophy and a top-performance high frequency transducer.

KEY FEATURES

- Two-way ABS speaker, 40 WRMS
- 6.5" woofer / 1" tweeter
- Built-in audio transformer for 70/100 V use
- Polypropylene woofer that resists heat and humidity
- Front grill may be removed for painting
- Aluminium front grill, rust-proof
- Clip-type input terminals and low impedance / high impedance power tap selector
- Cutting and painting templates included
- Support system with 3 rotating tabs
- Available in black or white finish

- EASE Win file available 


APPLICATIONS

- Corporate and residential buildings
- Commercial premises
- Leisure centres
- Sound reinforcement in clubs, bars, etc.
- Health and sports centres
- Meeting and conference rooms
- 5.1 and 7.1 surround systems
- Auditoriums, museums

TECHNICAL DATA

| | |
|------------------------------|--------------------------|
| Nominal low impedance | 8Ω |
| RMS power | 40W |
| 100V Power tap | 2,5 / 5 / 7,5 / 15W |
| 70V Power tap | 1,25 / 2,5 / 3,75 / 7,5W |
| Frequency response (-6dB) | 80Hz – 20kHz |
| Sensitivity 1W/1m | 88dB |
| External diameter | 204mm |
| Internal diameter | 178mm |
| Recommended cut out diameter | 180mm |
| Required depth | 73mm |
| Weight | 1,5Kg |

MECHANICAL DIAGRAMS



POLAR DIAGRAMS

